



## Mobil Super™ Synthetic

Mobil Passenger-Vehicle-Lube , United States

Full Synthetic Motor Oil

### Product Description

Mobil Super™ Synthetic motor oils are full synthetic, high performance formulations that outperform our conventional/synthetic blend oils and are designed to provide long engine life and outstanding protection in vehicles of all ages. Mobil Super Synthetic motor oils protect critical engine parts from lubricant related failures for up to 7,500 miles or your vehicle's OEM recommended oil change interval, whichever is longer\*, and meet warranty requirements where an American Petroleum Institute (API) certified oil is specified.

### Features and Benefits

Mobil Super™ Synthetic motor oils are full synthetic, high performance formulations that outperform our conventional/synthetic blend oils and are designed to provide long engine life and outstanding protection in vehicles of all ages.

Key features and potential benefits include:

Features	Advantages and Potential Benefits
Meets or exceeds the latest industry specifications	OEM warranty protection
Protects up to 400°F	Helps prevent oil breakdown during extended high temperature operation
High performance additives	Protects against wear and combat sludge and deposits
Warranty	Limited Warranty* offers protection for up to 7,500 miles or your vehicle's recommended oil change interval, whichever is longer
Full synthetic formula	Easy starting and rapid oil circulation during cold starts to protect critical engine parts
Tested, proven engine protection	Helps extend engine life

### Applications

Mobil Super™ Synthetic motor oils are recommended by ExxonMobil for all types of modern gasoline-powered vehicles, including high-performance turbocharged, supercharged, multi-valve, fuel injected engines found in passenger cars, SUVs, light vans and light trucks.

- Mobil Super Synthetic motor oils meet warranty requirements where an American Petroleum Institute (API) certified oil is specified.
- Mobil Super Synthetic oils are not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

Always check your owner's manual for the manufacturer's recommended oil viscosity grade, API service classification and any builder approval.

### Specifications and Approvals

This product has the following approvals:	0W-16	0W-20	5W-20	5W-30	10W-30
GM dexos1:GEN2 Licensed		X		X	

<b>This product is recommended for use in applications requiring:</b>	<b>0W-16</b>	<b>0W-20</b>	<b>5W-20</b>	<b>5W-30</b>	<b>10W-30</b>
Ford WSS-M2C945-A			X		
Ford WSS-M2C945-B1			X		
Ford WSS-M2C946-A				X	
Ford WSS-M2C946-B1				X	
Ford WSS-M2C947-A		X			
Ford WSS-M2C947-B1		X			
Ford WSS-M2C929-A				X	
Ford WSS-M2C930-A			X		
GM 6094M			X		X

<b>This product meets or exceeds the requirements of:</b>	<b>0W-16</b>	<b>0W-20</b>	<b>5W-20</b>	<b>5W-30</b>	<b>10W-30</b>
API SJ		X	X	X	X
API SL		X	X	X	X
API SM		X	X	X	X
API SN	X	X	X	X	X
API SN PLUS	X	X	X	X	X
API SN PLUS RESOURCE CONSERVING	X	X	X	X	X
API SN Resource Conserving	X	X	X	X	X
API SP		X	X	X	X
API SP Resource Conserving		X	X	X	X
ILSAC GF-6A		X	X	X	X
Chrysler MS-6395		X	X	X	X
FORD WSS-M2C960-A1			X		
FORD WSS-M2C961-A1				X	
FORD WSS-M2C962-A1		X			

#### Properties and Specifications

<b>Property</b>	<b>0W-16</b>	<b>0W-20</b>	<b>5W-20</b>	<b>5W-30</b>	<b>10W-30</b>
Grade	SAE 0W-16	SAE 0W-20	SAE 5W-20	SAE 5W-30	SAE 10W-30

Property	0W-16	0W-20	5W-20	5W-30	10W-30
Density @ 15 C, g/cm3, ASTM D4052	0.8366				
Density @ 15.6 C, g/ml, ASTM D4052		0.8455	0.8363	0.8504	0.8388
Flash Point, Cleveland Open Cup, °C, ASTM D92	222	231	220	238	236
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	6.7	8.4	8.3	10.9	10.3
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	29.9	43	47.0	62	62.0
Pour Point, °C, ASTM D97	-50	-45	-33	-36	-33

\*To learn more about the Mobil Super Limited Warranty, visit us at Mobil.US.

### Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2020

### Exxon Mobil Corporation

22777 Springwoods Village Parkway  
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved