



MileGuard™ High Mileage Synthetic Blend Motor Oil

MileGuard High Mileage Synthetic Blend Motor Oils are specially formulated for high mileage engines, especially those engines with over 50,000 miles. They are formulated to promote clean engines with excellent control of sludge and other engine deposits that form due to high engine temperatures and combustion exhaust. API SP provides emission system, turbocharger, LSPI and timing chain protection. Also helps to protect engines when operating on ethanol-containing fuels up to E85.

Benefits

- Reduces oil consumption and leaks
- Increases power output by maximizing compression
- Protects against thermal breakdown at high temperature
- Minimizes deposit and sludge formation
- Formulated for easy cold starts
- Fights friction
- ILSAC GF-6A Resource Conserving

Meets or Exceeds

- ILSAC GF-6A
- API Service Category SP, SN Plus, SN, SM, SL, SJ
- Ford WSS-M2C962-A1 (SAE 0W-20)
- Ford WSS-M2C960-A1 (SAE 5W-20)
- Ford WSS-M2C961-A1 (SAE 5W-30)
- Chrysler MS-6395 (SAE 5W-20, 5W-30, 10W-30)
- GM 6094M specification (SAE 0W-20, 5W-20, SAE 5W30 and SAE 10W30)
- Meets Toyota Specifications
- Meets Honda Service Fill Specifications



1211 Belmar Drive Belcamp, MD 21017
410-574-4500
www.tilleylubricants.com



MileGuard™ High Mileage Synthetic Blend Motor Oil

Typical Characteristics:

SAE Grade	5W-20	5W-30	10W-30
API Gravity @ 60°F	33.3	33.2	33.0
Sp. Gr. @ 60°F	0.8585	0.8591	0.8602
Flash, COC, °F	428	420	430
Pour Pt., °F	-38	-38	-30
Viscosity, cSt @ 40°C	51.8	62.1	62.8
Viscosity, cSt @ 100°C	8.7	10.5	10.2
Viscosity Index	147	159	149
API Service Category	SP	SP	SP
ILSAC	GF-6A	GF-6A	GF-6A



1211 Belmar Drive Belcamp, MD 21017
410-574-4500
www.tilleylubricants.com